



REVISION RECORD			
REV	ECN	DESCRIPTION	DATE

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited.
 未经允许禁止传输、复制、编辑该文档，以及利用其内容进行交流



Connection method:
 1. For Solid wire, peeling wire in right length, push down spring to clasp the wire.
 2. For stranded wire, connect directly after peeling in right length, or wire furrled and fix in by pushing the spring.

NOTES:
 UL/CUL Standard
 1. Conductor cross section : 26~12AWG
 2. Rated Voltage/Current :

Use group	B	C	D
Rated voltage(V)	600	600	
Rated current(A)	20	20	

IEC Standard
 1. Conductor cross section :

Wire range(Solid/Stranded)	0.2-2.5mm ²	0.2-4mm ²	0.2-2.5mm ²
Solid			
Stranded			
Stranded with ferrules			
Stranded with plastic sleeve			
Stranded with plastic sleeve with ferrules			

2. Rated Voltage/Current :

Surge voltage category	III
Pollution degree	3
Rated surge voltage(kV)	6
Rated voltage(V)	500
Rated current(A)	22

Material:

Insulator	P666	UL94 V-0
Conductor	Copper alloy	Sn plated
Spring	Stainless steel	
Conductor Piece	Copper alloy	Sn plated
Button	POM	

General information:

- Dimension shall be interpreted per ASME Y14.5-2009
- Stripping length : 10mm
- Operating temperature: -40°C~+105°C
- RoHS Compliance
- Undimensioned Tolerances:

Pitch Range in mm	Nominal Dimension	Range	Tolerance					
Over 6	Over 10	Over 30	Over 60	Over 100	Over 150			
To 10	To 24	To 30	To 60	To 100	To 150	±0.10		
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30	±2°

HOW TO ORDER:

TPD2.5-2-PV
 Series No. Color: PV: Black

订货号 Order No.	TPD2.5-2-PV	名称 Name	TP系列直插式 2.5mm ² 双层导线 两进两出接线端子	未注公差 Tolerance	表面 Surface
项目 Item	签字 Signature	图号 Drawing No.	PRM001478	版本号 Revision Number	VDI21
设计 Design	cjs	日期 Date	01/11/20 th	重量 Weight	比例 Scale
审核 Check	cw	材料 Material	Notes	M1	1:1
工艺 Process	-	物料号 Item No.	412211005	第1页/共1页 1 of 1	mm
标准化 Unity	-	NINGBO SUPU ELECTRONICS CO.,LTD.			
批准 Approve	1w1				

1 2 3 4 5 6 7 8